



priključci za traktor tuber  
tractor tuber attachments  
traktor tuber zubehörs

PV 3000

PV 4000



## Tehnički podaci

|                             | PV-2000             | PV- 3000                     | PV- 4000                     |
|-----------------------------|---------------------|------------------------------|------------------------------|
| Dimenzija sanduka:          | 1500x2500 mm        | 1800x3000 mm                 | 1800x3000 mm                 |
| Kipanje:                    | 3 strane            | 3 strane                     | 3 strane                     |
| Visina poda od tla:         | 884 mm              | 894 mm                       | 894 mm                       |
| Trag kotača:                | 1150 mm             | 1500 mm                      | 1500 mm                      |
| Sistem kočenja:             | hidraulički, zračni | hidraulički, zračni, naletni | hidraulički, zračni, naletni |
| Centralni sistem otvaranja: | stražnji i bočni    | stražnji i bočni             | stražnji i bočni             |
| Dopuštena brzina vožnje:    | 25 km/h             | 25 km/h                      | 25 km/h                      |
| Vlastita težina:            | 780 kg              | 900 kg                       | 960 kg                       |
| Kotači:                     | 10.0/80-12"         | 10.0/75-15,3"                | 10.0/75-15,3"                |
| Nosivost:                   | 2000 kg             | 3000 kg                      | 4000 kg                      |
| Opcija dodatnih stranica:   | 400 mm              | 400 mm                       | 500 mm                       |

## Technical features

|                         | PV-2000                             | PV-3000                             | PV-4000                             |
|-------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| Box dimensions:         | 1500x2500 mm                        | 1800x3000 mm                        | 1800x3000 mm                        |
| Tipping:                | 3 sides                             | 3 sides                             | 3 sides                             |
| Ground clearance:       | 884 mm                              | 894 mm                              | 894 mm                              |
| Track:                  | 1150 mm                             | 1500 mm                             | 1500 mm                             |
| Brakes:                 | hydraulic, air inertia brake system | hydraulic, air inertia brake system | hydraulic, air inertia brake system |
| Central locking system: | rear and side                       | rear and side                       | rear and side                       |
| Max. speed:             | 25 km/h                             | 25 km/h                             | 25 km/h                             |
| Weight:                 | 780 kg                              | 900 kg                              | 960 kg                              |
| Wheels:                 | 10.0/80-12"                         | 10.0/75-15,3"                       | 10.0/75-15,3"                       |
| Carrying capacity:      | 2000 kg                             | 3000 kg                             | 4000 kg                             |
| Optional side wall:     | 400 mm                              | 400 mm                              | 500 mm                              |

## Technische Merkmale

|                            | PV-2000   | PV-3000   | PV-4000   |
|----------------------------|---|---|---|
| Ladefläche:                | 1500x2500 mm                                    | 1800x3000 mm                                    | 1800x3000 mm                                    |
| Kippen:                    | 3 Seitenkipper                                  | 3 Seitenkipper                                  | 3 Seitenkipper                                  |
| Ladehöhe:                  | 884 mm  | 894 mm  | 894 mm  |
| Spurweite:                 | 1150 mm   | 1500 mm   | 1500 mm   |
| Bremse:                    | Hydraulisch<br>Luftbremssystem<br>Auflaufbremse | Hydraulisch<br>Luftbremssystem<br>Auflaufbremse | Hydraulisch<br>Luftbremssystem<br>Auflaufbremse |
| Verriegelung:              | Seitenwände und Heckklappe<br>Klappbar          | Seitenwände und Heckklappe<br>Klappbar          | Seitenwände und Heckklappe<br>Klappbar          |
| Ausführung:                | 25 km/h   | 25 km/h   | 25 km/h   |
| Gewicht:                   | 780 kg  | 900 kg  | 960 kg  |
| Bereifung:                 | 10.0/80-12"                                     | 10.0/75-15,3"                                   | 10.0/75-15,3"                                   |
| Ladekapazität:             | 2000 kg   | 3000 kg   | 4000 kg   |
| Optional aufsatzbordwände: | 400 mm  | 400 mm  | 500 mm  |